



Kvaser Leaf Professional SWC

EAN: 73-30130-00264-7

Kvaser Leaf Professional is a one channel, high performance, USB interface for Single Wire CAN. A versatile and powerful interface that offers easy connection between your PC and CANbus network, it includes Kvaser's patented MagiSync feature for synchronized time-stamping, Galvanic Isolation for protection against voltage spikes, and Auto Transmit for placing messages on the bus at set intervals.

Major Features

- Supports Single Wire CAN (SAE J2534)
- Automatic and accurate clock synchronization between several Kvaser Leaf Professional interfaces through Kvaser MagiSync™. The technical solution is unique and patented by Kvaser.
- Handles up to 20,000 messages per second, time-stamped and synchronized with a precision of 1 microsecond.
- Auto transmit buffers, to send messages on a defined interval.

- Auto response buffers, to send messages on a defined event.
- Supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifiers.
- Excellent error handling.
- Supports silent mode for analyzing tools.
- Low power consumption.
- Excellent EMC performance.
- Polyurethane cabling for extreme environments.
- Galvanic isolation of the CAN bus driver stage to protect the hardware.
- Labeled CAN channel for easy identification of the supported physical layer.
- Equipped with a 110 cm (44 in.) long USB cable and a 30 cm (12 in.) long CAN cable.
- Interfaces the CAN bus with a 9-pin D-SUB connector.
- Designed for USB 2.0, backward compliant with USB 1.1.
- Quick and easy Plug-and-Play installation.
- A practically unlimited number of Kvaser Leafs can be connected via standard USB hubs for simultaneous use on a single PC.

Warranty

- 2-Year Warranty. See our General Conditions and Policies for details.

Support

- Free Technical Support on all products available by contacting support@kvaser.com.

Software

- Documentation, software and drivers can be downloaded for free at www.kvaser.com/downloads.
- Kvaser CANLIB SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, and Visual Basic.

- All Kvaser CAN interface boards share a common software API. Programs written for one interface type will run without modifications on the other interface types!
- J2534 Application Programming Interface available.
- RP1210A Application Programming Interface available.
- On-line documentation in Windows HTML-Help and Adobe Acrobat format.

TECHNICAL DATA - KVASER LEAF PROFESSIONAL SWC

ON-BOARD RX BUFFER	Yes
# OF CAN CHANNELS	1
ON-BOARD TX BUFFER	Yes
CONNECTOR	DSUB 9
API, FREE	Kvaser API, J2534, RP 1210
WEIGHT (G)	100.0
TIMESTAMP RESOLUTION (US)	1
GALVANIC ISOLATION	Yes
CASING MATERIAL	-
API, LICENCED	None
ON-BOARD BUFFER	Yes
MAXIMUM BITRATE (KBPS)	100
HEIGHT (MM)	20
OPERATING SYSTEM	Linux,Win Vista,Win 10,Win 8,Win 7,Win XP
MINIMUM BITRATE (KBPS)	5
IP CLASS	N/A
RUGGED	No
CERTIFICATIONS	CE,RoHS
STATUS	Active
ERROR COUNTERS READING	No
SOUND	Yes
OPERATING TEMPERATURE RANGE (C)	-40.00 to 85.00
CLOCK SYNC	Yes
WIDTH (MM)	25
EMBEDDED SCRIPT	No
LENGTH (MM)	100
MSGRATE RX MAX	2000



Kvaser Leaf Professional SWC

MSGRATE TX MAX	2000
PC INTERFACE	USB
PRODUCT GROUPS	Leaf
NETWORK CHANNEL(S)	1 x CAN SWC
ERROR FRAME GENERATION	Yes
SILENT MODE	Yes
ERROR FRAME DETECTION	Yes

The information herein is subject to change without notice