



KVASER USBCAN PRO 2XHS V2 CB

EAN 73-30130-00877-9

The USBCan Pro 2xHS v2 CB is a bare circuit board version of Kvaser's USBCan Pro 2xHS v2 dual channel CAN or CAN FD interface with scripting capability. The USBCan Pro 2xHS v2 CB is supplied 'bare board' i.e. without a housing, and can thus be built into any system. The Pro version is shipped with Kvaser TRX, a lightweight development environment that lowers the bar when starting out programming the device.

KVASER USBCAN PRO 2XHS V2 CB

EAN 73-30130-00877-9

Major Features

- Supports CAN FD.
- Quick and easy plug-and-play installation.
- Supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifiers.
- Power derived from the USB connection, CAN or an in-built power supply.
- Galvanic isolation.
- High-speed CAN connection (compliant with ISO 11898-2), up to 1 Mbit/s.
- Fully compatible with J1939, CANopen, NMEA 2000 and DeviceNet.
- Kvaser MagiSync provides automatic time synchronization between several PC-to-bus interfaces connected to the same PC.
- Programming functionality to support interface mode e.g. Optimize protocol handling, pre-filter CAN messages directly on the interface, or simulate missing hardware.
- Simultaneous operation of multiple devices.



Technical Data

Bit Rate	50-1000 kbps
Temp Range	-40 - 85 °C
Time Stamp	1
Messages Per Second Receive	20000 mps
Messages Per Second Sending	20000 mps
Length	100 mm
Height	6 mm
Channels	2
Certificates	RoHS
Interfaces	USB
Categories	PC Interfaces, Interfaces
OS	Linux, Win Vista, Win 10, Win 8, Win 7, Win XP
Connectors	Molex 51021 PicoBlade™
Galvanic Isolation	Yes
Error Frame Generation	Yes
Error Counters Reading	Yes
Silent Mode	Yes
Sound	No
Current Consumption	max 500mA

WARRANTY

2-Year Warranty. See our General Conditions and Policies for details.

SUPPORT

Free Technical Support on all products available by contacting support@kvaser.com

SOFTWARE

Documentation, software and drivers can be downloaded for free at: www.kvaser.com/downloads

Units are shipped with Kvaser TRX, a lightweight development environment.

Kvaser CANlib SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation

and many program samples, written in C, C++, C#, Delphi, and Visual Basic.

All Kvaser CAN interface boards share a common software API. Programs written for one interface type will run without modifications on the other interface types!

J2534 Application Programming Interface available.

RP1210A Application Programming Interface available.

Online documentation in Windows HTML-Help and Adobe Acrobat format.